




BLACK BOX[®]

NETWORK SERVICES

ServSwitch Zero-Series



Key Features

- ▶ Simple plug and play auto-configure installation
- ▶ Add a server anywhere in the chain at any time
- ▶ Multi-platform Zero-CIMs-mix PCs, SUN, and USB
- ▶ Keep-alive keyboard/mouse emulation for flawless operation
- ▶ Hot connect a user console to any server
- ▶ Hot-swap components with no impact on server operation
- ▶ User Station supports both PS/2 and SUN user console
- ▶ Select computers by name from on-screen menus
- ▶ Automatic Video Tuning (AVT) adjusts video quality automatically
- ▶ Supports high-resolution video--to 1600x1200@60Hz
- ▶ Locate user up to 200m away from servers via Cat. 5 UTP cable
- ▶ Seamless interface to ServSwitch Paragon for clustered access to high-density servers

The innovative ServSwitch Zero-Series from BLACK BOX offers a switchless solution that enables access and control of multiple servers from a single user console (keyboard, monitor, and mouse), without consuming precious rack space. ServSwitch Zero-Series employs BLACK BOX's unique communication technology to control up to 42 servers and eliminate the traditional KVM switch box and all hard-to-manage server-to-server cable. It is designed to support the most challenging demands of server management where space is at a premium or where systems to be accessed are up to 200m away via Category 5 UTP cable.

ServSwitch Zero-Series replaces the traditional KVM switch-to-multiple-server cabling configuration with an innovative chain-like server-to-server arrangement, significantly reducing cable clutter. Small Computer Interface Modules (Zero-CIMs) connected to the keyboard, video, and mouse ports of each server are linked with standard Category 5 UTP cable and transmit the keyboard, video, and mouse signals to a User Station. A keyboard, monitor, and mouse (PS/2 or SUN) plug into the User Station, enabling the user to select and

control up to 42 servers via simple on-screen user interface menus. Since ServSwitch Zero-series components are plug and play, servers can be added at any time with no interruption of server operation.

ServSwitch Zero-Series is ServSwitch Paragon compatible for convenient, clustered access and control of high-density rack mounted servers in large-scale data centers. Connect the first Zero-CIM in the chain directly to BLACK BOX's ServSwitch Paragon with a single Category 5 UTP cable.

Specifications

User Station (receiver)

KVS802AE

Dimensions —

(HxWxD)44mmx290mmx255mm

Weight — 1.9 kg

Power — 100V/240V 50/60 Hz 5VA

ServSwitch Zero-Series Computer

Interface Modules (transmitters)

KVS802A-PC (for PC, incl. KVM-Port)

Dimensions —

(HxWxD)25mmx108mmx91mm

Weight — 0.3 kg

Power — (optional) 110V/240V 50/60 Hz 5VA

Ports — RJ45 in and out, plus local PC KVM port

For PC

KVS802A-P

Dimensions —

(HxWxD)25mmx62mmx89mm

Weight — 0.16 kg

Ports — RJ45 in and out

Black Box Network Services - The world's largest network services company

We are, with 25 years of experience, the world leader in network infrastructure services.

On the Phone — no charge, answer calls in less than 20 seconds, find the right product with our technical experts.

On-site — superior design and engineering, Certified installations, end-to-end service.

On-line — receive technical knowledge on-line, including technology overviews, BLACK BOX Explains and the Knowledge Box.

Most comprehensive TECHNICAL SUPPORT — our best Product! Free hotline TECH SUPPORT!

The world's best customer service — Custom design services and products, the best warranties, money-saving discount programs.

BLACK BOX exclusives — Certification Plus. Guaranteed-for-life products and services.

Ordering information

ITEM	CODE
Zero-User StationKVS802AE
Zero-PS/2 Interface ModuleKVS802A-P
Zero-PS/2 Interface Module KVMKVS802A-PL
Zero-SUN Interface ModuleKVS802A-S
Zero-TerminatorKVS802A-T
Zero-Starter Kit includes: 1 x KVS802AE, 3 x KVS802A-P 1 x KVS802A-TKVS802A-K