



Installation

This installation guide gives step-by-step instructions about how to install the LB9007C-ST

Selecting a combination for the plug-in module of LB9007C-ST

Fiber Plug-In Modules are available for Multi-mode with ST, SC, MT-RJ or VF-45 connectors and Single-mode with SC connectors. Certain modules are a combination of FX and TX ports, which accommodate either FX with ST, SC, MT-RJ or VF-45 connectors or TX with RJ-45 connectors.

Follow These Steps for Installation:

- Step 1:** Turn off the power before installation. Push the ON/OFF rocker switch to the 0 (OFF) position.
- Step 2:** Locate the module cover plate. It is located in the front of most models.
- Step 3:** Unscrew the plate and carefully remove it from the switch. A dummy module may be attached to the cover plate.
- Step 4:** Retain both the screws and the cover plate. The plate must be reinstalled if the module is removed.
- Step 5:** Slowly slide the Plug-In Module into the port, following the plastic guides.
- Step 6:** Snap in the Plug-In Module to attain a firm connection.
- Step 7:** Tighten the screws retained from original cover plate.
- Step 8:** Restore power.

CUSTOMER SUPPORT INFORMATION Order toll-free in the U.S. 24 hours, 7 A.M. Monday to midnight Friday: 877-877-BBOX
FREE technical support, 24 hours a day, 7 days a week: Call 724-746-5500 or fax 724-746-0746
Mail order: **Black Box Corporation**, 1000 Park Drive, Lawrence, PA 15055-1018
Web Site: www.blackbox.com ☞E-mail: info@blackbox.com